ROCKMAX® CURE A

HIGH PERFORMANCE CURING COMPOUND



INTRODUCTION

Rockmax Cure A is a high performance paraffin emulsion liquid curing compound. It can provide excellent curing film on concrete surface to prevent fast water evaporation. It is suitable to use with large concrete areas.

AREA OF USES

Rockmax Cure A mainly use in all concrete structures with no over coats on surface. It is widely use in large concrete structure and trafficable areas ie runways, highways, bridge desks, retaining walls, water storage areas, concrete towers, precast concrete girders and others.

ADVANTAGES

- High eliminate loss of water in concrete.
- Efficiency hydration reaction.
- Reduce shrinkage.
- Economical.
- Save labor cost.
- Non flammable.
- Non toxic.
- Can be over coat with other trades.

TECHNICAL PROPERTIES

Color and Form: white liquid

Specific Gravity: 0.97

Coverage rate: 5-8 m2/litre/coat

Drying time (at 30°C): 2 hours

SURFACE PREPARATION

Concrete surfaces must be sound and clean.

APPLICATION

Apply **Rockmax Cure A** by spray, roller or brushes. Apply immediately after remove formworks.

CLEANING

Clean all tools and equipments by clean water.

PACKAGING

200 litre drum.

STORAGE

Storage in shade and dry condition at 10-40°C. Avoid from sunlight, frost, water, moisture and high temperature.

SHELF LIFE

12 months if kept in original package and follow instructions.

PRECAUTIONS

Rockmax Cure A is not hazardous material. However avoid contact with skin and eyes. Safety goggles and gloves must be used during application. In case of skin of eye contact, rinse with plenty of water and see medical immediately. If swallowed must be see medical immediately. Do not induce vomiting. Good ventilation system must be used in case of unexposed areas. Rockmax Cure A is not flammable.

CONTACT DETAIL

THAILAND

Rockmax Company Limited

T: +66 2 8648658 F: +66 2 4184327 E: info@rockmax.net W: www.rockmax.net

VIETNAM

Viet Dai Viet Chemical Company Limited

T: +84862615184 F: +84862615185 E: rockmaxvn@gmail.com

IMPORTANTS NOTE!!

The technical information contained herein, while not guaranty, was prepared and approved by technical personnel and is true, accurate to the best of our knowledge. No warranty or guaranty is made regarding performance, stability or other factors beyond our control. Rockmax will welcome to be consultation of our performance and application. This technical datasheet supersedes and issue new edition without prior notice.

