

ROCKMAX[®] MESH

FIBERGLASS MESH FOR WATERPROOFING APPLICATION



INTRODUCTION

Rockmax Mesh is a fiberglass mesh use in waterproofing application. The mesh increases reinforced, tensile, adhesion and puncture resistance to waterproofing system.



AREA OF USES

Rockmax Mesh can be used with variety of waterproofing materials such as Acrylic, Ceramic, Polyurethane, Cement flexible, Liquid Modified Bitumen Waterproofing.

ADVANTAGES

- Increase Puncture resistance.
- Increase adhesion to substrate.
- Good bonding between waterproofing material layers.

TECHNICAL PROPERTIES

Color: White

Width x Length: 1 meter x 100 meter

Thickness: approx 0.22mm

PACKAGING

Roll: 1meter width x 100 meter length.

STORAGE

Storage in shade and dry condition at 10-30°C.
Avoid from sunlight, UV, frost, water, moisture and high temperature.

SHELF LIFE

24 months if kept follow instructions.

PRECAUTIONS

Rockmax Mesh is not hazardous during normal condition use. It is recommended to take the safety standard and precaution for application and storage.

CONTACT DETAIL

THAILAND

Rockmax Company Limited

T: +66 2 8648658

F: +66 2 4184327

E: info@rockmax.net

W: www.rockmax.net

VIETNAM

Viet Dai Viet Chemical Company Limited

T: +84 86 2615184

F: +84 86 2615185

E: rockmaxvn@gmail.com

IMPORTANT NOTE!!

The technical information contained herein, while not guaranty, was prepared and approved by technical personnel and is true, accurate to the best of our knowledge. No warranty or guaranty is made regarding performance, stability or other factors beyond our control. Rockmax will welcome to be consultation of our performance and application. This technical datasheet supersedes and issue new edition without prior notice.
