

# ROCKMAX<sup>®</sup> NEX L

## LIQUID FLOOR HARDENER



### INTRODUCTION

**Rockmax Nex L** is a liquid type floor hardener and sealer. The cured product forms a hard wearing surface including with dust proof surface.

### AREA OF USES

**Rockmax Nex L** can be used for old and new concrete floors. The application areas include car parks, warehouses, laboratories, etc.

### ADVANTAGES

- Replace old traditional powder form.
- Good impact resistance surface.
- Dust proofer.
- Penetrate into concrete floor.
- Reduce damaged floor area by apply at the latest state of construction.
- No-debond.

### TECHNICAL PROPERTIES

Color: clear

Form: liquid

Specific gravity: 1.1-1.15 kg/litre

Coverage rate: 4-5L/m<sup>2</sup>

### PREPARATION

Concrete surface must be clean, sound and dry. Free from oil, dust, cement paste, laitance, mould oil and any particles. Concrete must be at least 28 days old.

### APPLICATION

Apply **Rockmax Nex L** by spray direct to the concrete surface. Use plastic brush to spread the material over the surface areas. The minimum 2 coats is required.

### CURING

Curing by moist. Spray water similar as concrete curing.

### CLEANING

Clean all tools and equipments immediately with water.

### PACKAGING

25Litre.

### STORAGE

Storage in shade and dry condition. Avoid from frost, water, moisture and high temperature.

### SHELF LIFE

12 months if kept follow instructions.

### PRECAUTIONS

Avoid contact with skin and eye. Safety and hygiene should be followed.

### CONTACT DETAIL

THAILAND

**Rockmax Company Limited**

T: +66 2 8648658

F: +66 2 4184327

E: info@rockmax.net

W: www.rockmax.net

VIETNAM

**Viet Dai Viet Chemical Company Limited**

T: +84 86 2615184


F: +84 86 2615185

E: rockmaxvn@gmail.com

---

### IMPORTANT NOTE !!

*The technical information contained herein, while not guaranty, was prepared and approved by technical personnel and is true, accurate to the best of our knowledge. No warranty or guaranty is made regarding performance, stability or other factors beyond our control. Rockmax will welcome to be consultation of our performance and application. This technical datasheet supersedes and issue new edition without prior notice.*

 Printed on recycled paper  
Copyright©2009 Rockmax