

ROCKMAX[®] PU PRIMER

PRIMER FOR POLYURETHANE SEALANT



INTRODUCTION

Rockmax PU primer is a ready to use, one part primer for polyurethane sealant.

AREA OF USES

Rockmax PU primer can be used as primer for porous substrate before apply polyurethane sealant.

ADVANTAGES

- Can be applied on moist substrate.
- Easy to use.

TECHNICAL PROPERTIES

Color: Clear
Form: Liquid
Density: ~0.95 kg/m³
Pot life (at 30 °C): 30 minutes
Touch dry (at 30 °C): 90-120 minutes
Consumption: 0.15 – 0.20 kg/m²
Application Temperature: +5°C to +45°C

APPLICATION

Apply **Rockmax PU Primer using** by brush. Allow the material to dry approximate 2-3 hours prior to apply sealant.

PACKAGING

1kg.
17kg.

STORAGE

Storage in shade and dry condition. Avoid from frost, water, moisture and high temperature (min-max 5-40°C). Do not expose to sun light.

PRECAUTIONS

Keep away from open flame. Work on ventilated area only. Avoid contact with skin and eye. Goggle and glove must be use while application. Clean with plenty of water when contact with and see doctor as quick as possible. MSDS is available upon request.

CONTACT DETAIL

THAILAND

Rockmax Company Limited

T: +66 2 8648658

F: +66 2 4184327

E: info@rockmax.net

W: www.rockmax.net

VIETNAM

Viet Dai Viet Chemical Company Limited


T: +84 86 2615184

F: +84 86 2615185

E: rockmaxvn@gmail.com

IMPORTANT NOTE!!

The technical information contained herein, while not guaranty, was prepared and approved by technical personnel and is true, accurate to the best of our knowledge. No warranty or guaranty is made regarding performance, stability or other factors beyond our control. Rockmax will welcome to be consultation of our performance and application. This technical datasheet supersedes and issue new edition without prior notice.

 Printed on recycled paper
Copyright©2012 Rockmax